

Anchor plug M12 / 16mm x 50mm - leave in wall (Box of 50pc)



Code:MDX-FIX-APM12-16

website: <http://www.holer.co.nz/Product/info/MDX-FIX-APM12-16>

BarCode: 9420050726537

Description: Drop-In Anchor is an all Carbon Steel, Stainless Steel 316 (A4), medium duty, displacement setting, expansion anchor designed to provide a permanent anchorage point in concrete. Its internal thread allows it to be used with both machine bolts and threaded rod, placing no restrictions on fixture thickness. Requires the use of the correct setting tool (punch) to ensure full expansion of the anchor body. The setting tool (punch) also acts as visual check for correct setting of the anchor. Indicative working loads in 32MPa Concrete: Max Tensile 2.5kN – 15.8kN, Max Shear 2.2kN – 13.1kN. Fits flush with, or just below, the surface of the substrate, leaving no protrusions when not in use and allowing for easy patch work.

Drop-In Anchor is an all Carbon Steel, Stainless Steel 316 (A4), medium duty, displacement setting, expansion anchor designed to provide a permanent anchorage point in concrete. Its internal thread allows it to be used with both machine bolts and threaded rod, placing no restrictions on fixture thickness. Requires the use of the correct setting tool (punch) to ensure full expansion of the anchor body. The setting tool (punch) also acts as visual check for correct setting of the anchor. Indicative working loads in 32MPa Concrete: Max Tensile 2.5kN – 15.8kN, Max Shear 2.2kN – 13.1kN. Fits flush with, or just below, the surface of the substrate, leaving no protrusions when not in use and allowing for easy patch work.

Specifications

Quality	Premium***
L x W x H	0.000000 x 0.000000 x 0.000000mm
Volume	0.000000m ³
Weight	2.700000kg
DK	A